

# Характеристики



Фото репрезентативне

## Eaton 167348

Main load disconnecter Switch with isolation function, highly wear resistant contacts, 240/415 V, 25 A, 3P

### General specifications

<b>PRODUCT NAME</b>	Eaton HIS Disconnector
<b>CATALOG NUMBER</b>	167348
<b>EAN</b>	4015081638482
<b>PRODUCT LENGTH/DEPTH</b>	60 mm
<b>PRODUCT HEIGHT</b>	80 mm
<b>PRODUCT WIDTH</b>	53.1 mm
<b>PRODUCT WEIGHT</b>	0.305 kg
<b>COMPLIANCES</b>	RoHS conform
<b>MODEL CODE</b>	HIS-25/3



Powering Business Worldwide

## Характеристики продукту

<b>DEGREE OF PROTECTION</b>	IP40 IP10
<b>TERMINALS</b>	Lift terminal
<b>IMPRINT/INDICATION</b>	Symbol "arrows"
<b>LAMP SOCKET</b>	Other
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-5 °C
<b>BUILT-IN DEPTH</b>	69.5 mm
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0.8 W
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>AMPERAGE RATING</b>	25 A
<b>COLOR CALOTTE</b>	Other
<b>SWITCH TYPE</b>	Off switch
<b>RATED SHORT-TIME WITHSTAND CURRENT (ICW)</b>	1 kA
<b>VOLTAGE TYPE</b>	AC
<b>LAMP TYPE</b>	Other
<b>TYPE</b>	HIS. Main load disconnect switch
<b>APPLICATION</b>	Switchgear for residential applications
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	3
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	25 A
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	415 V
<b>RATED SWITCHING CAPACITY</b>	12.5 kA
<b>VOLTAGE RATING - MIN</b>	240 V
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	3
<b>NUMBER OF POLES</b>	Three-pole

## Ресурси

КРЕСЛЕННЯ

[eaton-dimensions-mas-is.jpg](#)

---

**НАЗВА ПРОЕКТУ:**

**НОМЕР ПРОЕКТУ:**

**ПІДГОТУВАВ:**

**ДАТА:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Дублін 4, Ірландія  
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.

